

## § 230.7

Stat. 913, as amended, 49 U.S.C. 20702, applicable to one or more steam locomotives, shall lapse on January 18, 2000 unless a copy of the grant of waiver is filed for reassessment prior to that date with the Office of Safety, Federal Railroad Administration, 400 Seventh Street, Washington, DC 20590. FRA will review the waiver and notify the applicant whether the waiver has been continued.

### § 230.7 Responsibility for compliance.

(a) The locomotive owner and/or operator is directly responsible for ensuring that all requirements of this part are satisfied, and is the entity primarily responsible for compliance with this part.

(b) Although the duties imposed by this part are generally stated in terms of the duties of a railroad or a steam locomotive owner and/or operator, any person, including a contractor for a railroad, who performs any function covered by this part must perform that function in accordance with this part.

(c) Chapter 207 of Title 49 of the United States Codes makes it unlawful for any railroad to use or permit to be used on its line any steam locomotive or tender unless the entire steam locomotive or tender and its parts and appurtenances are in proper condition and safe to operate in the service to which they are put, without unnecessary danger of personal injury and have been inspected and tested as required by this part.

### § 230.8 Definitions.

As used in this part, the terms listed in this section have the following definitions:

*Administrator.* The Administrator of the Federal Railroad Administration or the Administrator's delegate.

*Alteration.* Any change to the boiler which affects its pressure retention capability. Rating changes are considered alterations.

*ANSI.* American National Standards Institute.

*API.* American Petroleum Institute.

*ASME.* American Society of Mechanical Engineers.

*Boiler surfaces.* The boiler interior is all the space inside a boiler occupied by water or steam under pressure, and

## 49 CFR Ch. II (10–1–07 Edition)

all associated surfaces inside that space exposed to that water and steam. The boiler exterior is the opposite surface of all components directly exposed to the boiler interior. This includes the fire side of the firebox sheets.

*Break.* A fracture resulting in complete separation into parts.

*Code of original construction.* The manufacturer's or industry code in effect when the boiler was constructed. If the exact code is not known, the closest contemporary code may be used provided it does not pre-date the construction date of the boiler.

*Crack.* A fracture without complete separation into parts, except that castings with shrinkage cracks or hot tears that do not significantly diminish the strength of the member are not considered to be cracked.

*Dead locomotive.* A locomotive unable to produce tractive effort.

*Fire.* Anything that produces products of combustion that heat transferring components of the locomotive are exposed to.

*FRA.* The Federal Railroad Administration.

*Locomotive operator.* Person or entity which operates, but which does not necessarily own, one or more steam locomotives. This term means, for purposes of inspection and maintenance responsibility, the entity responsible for the day-to-day operation of the steam locomotive, or the delegate thereof. This entity may be a railroad or a person or persons who operate a steam locomotive under contract for a railroad.

*Locomotive owner.* Person or entity which owns, but which does not necessarily operate, one or more steam locomotives that is operated on a railroad to which this part applies. For purposes of inspection and maintenance responsibility, this term includes that entity's delegate as well.

*MAWP.* Maximum allowable working pressure as specified by the steam locomotive specification FRA Form No. 4. (See appendix C of this part.)

*NBIC.* National Board Inspection Code published by the National Board of Boiler and Pressure Vessel Inspectors.

*NDE.* Non-destructive Examination.

*NPS.* Nominal Pipe Size.